

Standard Fitting Dimensions

Width:	1-5/8"	(41.3 mm)
Thickness:	1/4"	(6.3 mm)
Hole Diameter:	9/16"	(14.3 mm)
Hole Spacing On Center:	1-7/8"	(47.6 mm)
Hole Spacing From Ends:	13/16"	(20.6 mm)
Metrics in Parenthesis		
•Unless Otherwise Specified•		

VERSABAR CORPORATION

FLAT FITTINGS



VF-1409 Wt/ea .93 Lbs. (.420 kg.) 	VF-1412 Wt/ea .8 Lbs. (.360 kg.) 	VF-1402 Wt/ea .77 Lbs. (.348 kg.) 	VF-1406-A Wt/ea .8 Lbs. (.360 kg.)
VF-1406 Wt/ea 1.07 Lbs. (.490 kg.) 	VF-1406-B Wt/ea .64 Lbs. (.291 kg.) May be produced from 3/16" (4.8 mm) thick bar, check with factory.	VF-1401 Wt/ea .83 Lbs. (.375 kg.) 	VF-1401-B Wt/ea .61 Lbs. (.278 kg.)
VF-1411 Wt/ea 1.1 Lbs. (.5 kg.) 	VF-1404 Wt/ea 1.0 Lbs. (.454 kg.) 	VF-1403 Wt/ea 1.0 Lbs. (.454 kg.) 	VF-1419 Wt/ea 2.68 Lbs. (1.22 kg.)
VF-1501 Wt/ea 1.05 Lbs. (.474 kg.) 	VF-1501-B Wt/ea 1.05 Lbs. (.474 kg.) * Outside holes 1-3/16" (30) center to end	VF-1505 Wt/ea 1.5 Lbs. (.678 kg.) 	VF-1504 Wt/ea 1.5 Lbs. (.678 kg.)