

## W5461-T0W


Weather- and Tamper-Resistant Single Receptacle, 20 Amp 250 Volt, White

Single Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Weather- and Tamper-Resistant, Smooth Face, 20 Amp, 250 Volt, Back and Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton's 250 Volt Tamper-Resistant Receptacles are the industry's first and only solution to the revisions of the NEC Article 406.12! These weather-resistant single receptacles also provide compliance for Article 406.9 of the National Electrical Code (NEC) for wet and damp locations and include added protection against corrosion, UV degradation and cold impact damage.

- Accommodates back and side wiring
- Nickel-plated steel strap maximizes corrosion resistance
- Brass-self grounding clip is permanently staked on for secure and reliable performance
- Common applications: education facilities, commercial buildings, health care facilities, hospitality, and multiple dwelling units (MDUs)




Color :  White

UPC Code : 078477101728

Country Of Origin : Mexico

RoHS Compliant : Yes



### Available Colors :



### Technical Information

#### Electrical Specifications

**Amperage** : 20 A  
**Dielectric Voltage** : 2000 VAC  
**Grounding** : Self-Grounding  
**HP Rating** : 2 HP  
**Pole** : 2  
**Temperature Rise** : Max 30 C  
**Voltage** : 250 VAC  
**Wire** : 3

#### Environmental Specifications

**Flammability** : Rated V-2 per UL 94  
**Operating Temperature** : Maximum Continuous 75°C, minimum -40°C (w/o impact)

#### Material Specifications

**Body Material** : Nylon  
**Face Material** : PBT  
**Ground Contacts** : Phosphor Bronze  
**Grounding Screw** : #8 Brass  
**Line Contacts** : Brass Triple Wipe 0.040"  
**Mounting Screws** : #6 Stainless Steel

**Mounting Strap** : Nickel-Plated Steel

**Tamper Resistant Shutter Mechanism** : Thermoplastic

**Terminal Clamps** : Brass

**Terminal Screws** : #10 Brass

#### Mechanical Specifications

**Product ID** : Ratings are Marked on Device

**Screw Terminal Torque** : 10-14 in-lbs

**Terminal Accom.** : #14-#10 AWG Solid or Stranded

**Termination** : Back & Side Wire

#### Product Features

**Color** : White

**Device Type** : Single Receptacle Outlet

**Feature** : Weather- and Tamper-Resistant , Smooth Face , RoHS Compliant

**Grade** : Heavy-Duty Industrial Specification Grade

**NEMA** : 6-20R

#### Standards & Certifications

**NEMA Rating** : WD-1 and WD-6

**Standards and Certifications** : UL 498; CSA C22.2, No. 42; Fed Spec WC-596; NOM

#### Warranty

**Warranty** : 10-Year Limited

## SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

