WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

WL-LED120

Step And Wall Light

Model & Voltage	*Color Temp & CRI*	*Lumens*	*Finish*
❍ WL-LED120 120 VAC	❍ Amber 90	36	❍ BK Black on Aluminum
	❍ White 90	36	❍ BZ Bronze on Aluminum
❍ WL-LED120F 277 VAC	❍ Amber 90	36	❍ WT White on Aluminum
	❍ White 90	36	

Example: **WL-LED120-AM-BK**

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- Louvered design offers shielded illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast corrosion resistant aluminum alloy
Power:	3W, 3.5W
Input:	120 VAC, 277 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
Rated Life:	50000 Hours
Mounting:	Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x 2"W x 2.5"D
Finish:	Enamel Coated Bronze on Aluminum, Enamel Coated White on Aluminum, Enamel Coated Black on Aluminum
Operating Temp:	-40°F to 104°F (-40°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA, Title 24 JA8-2016 Compliant

FINISHES

Black on Aluminum | Bronze on Aluminum | White on Aluminum

LINE DRAWING



REPLACEMENT PARTS

W-4051-120-BZ - LED120 Cover Plate BZ
W-4051-120-WT - LED120 Cover Plate WT
W-4051-120-BK - LED120 Cover Plate BK
4MT2-S927-BK - 4MT2-N930-BK
4MT2-S930-BK - 4MT2-N935-BK
4MT2-S935-BK - 4MT2-N940-BK
4MT2-S940-BK - 4MT2-F927-BK
4MT2-N927-BK - 4MT2-F930-BK