## W TRACK 120V/277V SURFACE MOUNT TWO CIRCUIT ARCHITECTURAL TRACK





## 120V/277V TRACK SECTIONS

Model		Length		Finish	
WT	120V	4	4'	BK	Black
WHT		8	8'	PT	Platinum
WITI	277V	12	12'	WT	White

Example: WHT4-PT

Each section includes two matching end caps.

ACCESSOR	ES	Model	Volt	Finish	Description				_		= Indicates Electrical Continuity	
Live End Connector - Left		WEDL WHEDL	120V 277V	BK PT	Direct wiring through ceiling. Polarity on left side of track	"L" Connector		WLLC WHLLC	120V 277V		Join 2 track sections to make power feedable 90° left polarity turns.	
Live End Connector - Right		WEDR WHEDR	120V 277V	WT	Direct wiring through ceiling. Polarity on right side of track					BK PT		
"I" Connector	0	WPC WHPC	120V 277V	BK PT WT	Join two sections of track with electrical continuity.	"L" Connector – Right		WRLC WHRLC	120V 277V	WT	Join 2 track sections to make power feedable 90° right polarity turns.	
"I" Power Connector		WIC WHIC	120V 277V	BK PT WT	T Power entry point at the connection of two tracks.   "T" Connector <b>WLTC</b> 120V		Join 3 track sections. Power feedable. Polarity on outside edae.					
Flexible		WFC	120V	вк	Transition from wall-to-wall, wall-to-ceiling, or	WHLIC	VHLTC 277V Bk		,			
Connector		WHFC	277V	PT WT	ceiling-to-ceiling. Power feedable.	"T" Connector		WRTC	120V 277V	WT	Join 3 track sections. Power feedable.	
Canopy Plate		СР	120V 277V	BK PT	Covers a standard 4" octagonal box.	– Right		WHRTC	2//V		Polarity on inside edge.	
End Cap		WEC	120V 277V	WT BK			X	WXC WHXC	120V 277V	вк	Join 4 track sections. Power feedable.	
	Y			PT WT		"X" Connector				PT WT		

SUSPENSION	Model	Length	Finish	Description	SUSPENSION ACCESSORIES	Model	Finish
Stem Kit With Power Feed	WMSP	6 6" 12 12" 24 24" 36 36"	BK PT WT	Power feed to connect with a Live End or any Joiner/Feeder. Field cuttable.  Flexible power feed to connect with a Live End or any Joiner/Feeder. Recommended for use with Cable	"I" Power Connector Suspension Mount	WMPC	BK PT WT
Flexible	<b></b>	<b>48</b> 48" <b>96</b> 96" <b>48</b> 48"	вк		Power Feed Coupler Suspension Mount Use with "I" power connector	WMIC	BK PT WT
Power Feed	WMFP	<b>96</b> 96"	PT WT		Connector		
Pendant Stem Kit	WMT-X	6 6" 12 12" 24 24"	вк	Suspensions. Field cuttable.  Suspend track from the ceiling. Field cuttable.	Live End Suspension Mount	WMED	BK PT WT
T–Bar Stem Kit	WMT-TB	36 36" 48 48" 96 96"	WT	Suspend from drop ceilings. Field cuttable.	"L" Connector Suspension Mount	WMLC	BK PT WT
Sloped Ceiling Stem Kit	WMT	XS6 6" XS12 12" XS24 24" XS36 36" XS48 48"	BK PT WT	Suspend track from a sloped ceiling. Field cuttable.	"T" Connector Suspension Mount	WMTC	BK PT WT
Sloped Ceiling Cable Kit	WMST	XS96 96" XS48 48" XS96 96"	BK PT WT	Suspend track from a sloped ceiling. Field cuttable.	"X" Connector Suspension Mount	WMXC	BK PT WT
Suspension Cable Kit	WMST-X	<b>48</b> 48"	BK PT WT	Suspend track from the ceiling. Field cuttable.	Suspension	WMT	BK PT
T–Bar Suspension Cable Kit	WMST-TB	<b>96</b> 96"		Suspend track from drop ceilings. Field cuttable.	Hanger Clip		WT