

Weather Non-Tamper Resistant GFCI 15A/20A

 Share



Specification Grade - Weather Resistant Duplex GFCIs are built to meet every need in commercial, industrial and institutional settings, whether permanent or temporary – and is fully compliant with the latest UL943 standards for GFCIs. Complies with 2011 NEC Article 406.9 that states that all receptacles installed in wet or damp locations must be weather resistant. Weather Resistant Receptacles offer protection from rain, snow, ice, moisture, and humidity when properly installed in an approved weather protective or while-in-use cover. Weather resistant receptacles are for use in any residential or commercial outdoor location. Designed with enhanced nylon and corrosion resistant metal components Weather resistant receptacles are extra durable. Combine WR receptacles with any of our WeatherBox While-in-Use Protective Covers for tough protection against the elements.

- ▶ [Tamper Resistant Brochure](#)
- ▶ [ArrowLink Tamper & Weather Resistant GFCI Receptacles Spec Sheet](#)
- ▶ [Wiring instructions](#)

PRODUCT DETAILS

RESOURCES

Catalog Number	WRVGF15, WRVGF20
Wiring Method	Back Wire & Side Wire
Rating	15A 125V NEMA 5-15R, 20A 125V NEMA 5-20R
Weather Resistant	2008 NEC Article 406.11 Compliant
Product Colors	Colors may vary per product. For ordering, include Cat No. followed by the color code: B (Brown), GY (Gray), V (Ivory), W (White).

FEATURES

- ShockSentry lock-out function protects from miswired line load connections and GFCI circuitry damage.
- Large visual indicator light provides quick visual reference of a tripped or “end of life” condition.
- Weather Resistant models comply with 2011 NEC Article 406.9 that states that all receptacles installed in wet or damp locations must be weather resistant.
- Longer, wider “bridged” strap provides 40% more contact area with wallboard, virtually eliminating floating installations.