

Verve

Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

N	Nodel & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
	WS-W17714 14"	3000K 90	AL Brushed Aluminum BK Black WT White	23W	1200	600	Yes

Example: WS-W17714-WT

•For 277V special order, add an "F" before the finish: WS-W17714F-AL

For custom requests please contact customs@waclighting.com

DESCRIPTION

Signature minimalism, Verve mounts well vertically or horizontally as an elongated sconce with up and down illumination. A seamless exterior makes for a clean design. Verve features asilk-screened diffuser with a white ceramic glaze and a light engine that is factory sealed for maximum protection against the harshest elements.

FEATURES

- Up & down light
- Conversion plate for 4" junction box included
- Silk-screened diffuser with a white ceramic glaze
- · Seamless exterior makes for a clean design
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations


Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed


Construction: Aluminum hardware with glass diffuser



FINISHES:



LINE DRAWING:



WS-W17714



Verve

Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size		Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
WS-W17726	26"	3000K 90	AL Brushed Aluminum BK Black WT White	46W	2450	1215	Yes

Example: WS-W17726-WT

•For 277V special order, add an "F" before the finish: WS-W17726F-AL

For custom requests please contact customs@waclighting.com

DESCRIPTION

Signature minimalism, Verve mounts well vertically or horizontally as an elongated sconce with up and down illumination. A seamless exterior makes for a clean design. Verve features asilk-screened diffuser with a white ceramic glaze and a light engine that is factory sealed for maximum protection against the harshest elements.

FEATURES

- Up & down light
- Conversion plate for 4" junction box included
- Silk-screened diffuser with a white ceramic glaze
- · Seamless exterior makes for a clean design
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 54000 Hours

Mounting: Can be mounted on ceiling or wall in all orientations


Standards: ETL, cETL, IP65, Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum hardware with glass diffuser



FINISHES:



LINE DRAWING:

