

WAC LIGHTING

Tube

Single & Double Wall Mount 3000K

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
WS-W2604 5" - 2 Lights	3 3000K 90	33W	2312	AL Brushed
	3 3000K 90	16W	1091	Aluminum
WS-W2605 5" - 1 Light				BK Black
				BZ Bronze
				GH Graphite
				WT White

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **WS-W2604-AL**

FEATURES

- 2605 Single, 2604 Double
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast Aluminum
Power:	16W, 33W
Input:	120-277V, 50/60Hz
Dimming:	ELV: 100-10% , 0-10V: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Rated Life:	70,000 Hours
Mounting:	Mounts directly to junction box, Can be mounted on wall in all orientations
Finish:	Electrostatically Powder Coated: Brushed Aluminum with Clear Powder Coat Brushed Aluminum, Powder Coat Bronze Bronze, Black, Powder Coat Graphite Graphite, Powder Coat White White
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	ETL, cETL, Wet Location Listed, IP65, Title 24 JA8 Compliant



FINISHES:

