



YS10WAG1, Compression Splice, AL9CU, #14-10 AWG

By Burndy
Catalog # [YS10WAG1](#)



AL Splice, AL9CU, Internal Chamfer, Tin Plated, Prefilled
PENETROX™ A13 oxide inhibitor, End Cap, UL/CSA, 90°C, Up to
35kV, Color Code, Die Index.

Application

Wire Splice

General

Catalog Number	YS10WAG1
Connector Type	DUAL RATED
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Long
Finish Type	Tin-Plated
Material	ALUMINUM
Plated	N
Plating Type	Unplated
Temperature Rating	194
Trade Name	HYLINK™
UPC	781810744758
UPC 12 Digit	7818107447588

Dimensions

Dimension - B Length fraction	1/2 in
Dimension - B Length inch	0.50 in
Dimension - L Length Overall mm	28.45 mm
Dimension - Length Overall inch	1.12 in
Dimension - Outside Diameter inch	0.21 in
Dimension - Strip Length inch	5/8

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - AL Str Size	14-10 AWG
Conductor - AL Str Size Range	10 AWG
Conductor - Copper Solid Size	10 AWG
Conductor - Copper Str Size	14-10 AWG
Conductor - Copper Str Size Range	14 AWG - 10 AWG
Conductor - Material	ALUMINUM / COPPER
Conductor Size	14-10 AWG
Conductor Type	CODE
Wire Size	14-10 AWG

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	20
Minimum Pack Quantity	20

Product Assets

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Catalogs - BURNDY Master Catalog - Section C - Compression Connections](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Sales Drawings - SC081377-01](#)
[Specifications - YS10WAG1](#)



A Hubbell brand