



YSR44FX34LTCKITC, Compression Splice Reducer, Barrel A 750 kcmil, Barrel B 500 kcmil, includes clear heat shrink

By Burndy
Catalog # [YSR44FX34LTCKITC](#)



CU Splice Reducer, Barrel A 750 kcmil G,H,777 DLO, Barrel B 500 kcmil, Standard Barrel, Internal Chamfer, Tin Plated, Connector is UL/CSA, 90°C Up to 35kV, Kit comes with Clear Heat Shrink, Yellow/Brown Color Code, L115/20 Die Index.

Application

Wire Reducing Splice

General

Catalog Number	YSR44FX34LTCKITC
Color Code	Yellow, Brown
Color Code - Side A	Yellow
Color Code - Side B	Brown
Connector Type	STANDARD BARREL KITS
Die Index	L115/20
Die Index - Element A	L115
Die Index - Element B	20
Die Index Run Side	L115
Die Index Tap Side	20
Feature - Barrel Style	Skived
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Trade Name	HYREDUCER™
UPC	781810344330
UPC 12 Digit	7818103443300

Dimensions

Dimension - B Length fraction	2-1/16 in
Dimension - B Length inch	2.09 in
Dimension - L Length Overall mm	125 mm
Dimension - Length BB inch	1.69 in
Dimension - Length Overall inch	4.91 in
Dimension - Strip Length inch	1.96 in

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper Flex G Run	750 KCMIL
Conductor - Copper Flex G Size A	750 kcmil
Conductor - Copper Flex G Size A Range	750 kcmil
Conductor - Copper Flex H Run	750 KCMIL
Conductor - Copper Flex H Size A	750 kcmil
Conductor - Copper Flex H Size A Range	750 kcmil
Conductor - Copper Flex I Run	750 KCMIL
Conductor - Copper Flex I Size A	750 KCMIL
Conductor - Copper Flex I Size A Range	750 KCMIL
Conductor - Copper Flex K Run	750 KCMIL
Conductor - Copper Flex K Size A	750 KCMIL
Conductor - Copper Flex K Size A Range	750 KCMIL
Conductor - Copper Flex M Run	750 KCMIL
Conductor - Copper Flex M Size A	750 KCMIL
Conductor - Copper Flex M Size A Range	750 KCMIL
Conductor - Copper Str Size	750 KCMIL-350 KCMIL
Conductor - Copper Str Size A	750 kcmil
Conductor - Copper Str Size A Range	750 kcmil
Conductor - Copper Str Size B	500 kcmil
Conductor - Copper Str Size B Range	500 kcmil
Conductor - Material	COPPER
Conductor Size	750 KCMIL-350 KCMIL
Conductor Type	FLEX
Wire Size	750 KCMIL-350 KCMIL

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Carton Quantity	6
Minimum Pack Quantity	6
Pallet Quantity	540

Product Assets

- Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
- Catalogs - BURNDY Master Catalog - Section C - Compression Connections
- Customer Notices - Prop 65 Notice
- Installation Manuals - SPLICE KIT trilingual
- Interactive Catalog - BURNDY Full-Line Digital Catalog
- Sales Drawings - 10021428
- Specifications - YSR44FX34LTCKITC



A Hubbell brand