
# **Wiring Space**


#### **Typical Panelboard**

Front view with trim removed




# Typical Front w/Concealed Hinges and Trim Adjusting Screws

Surface mounting – add 1/4" to inside box dimensions Flush mounting – add 1 1/2" to inside box dimensions



#### Typical Box



# Minimum Wiring Space, From End of Lug to Box Wall, in Inches

	Main rating in amps	Ena wali		Frame		Main Circuit Breaker Phase Lug
		<b>Phase Lug</b>	<b>Neutral Lug</b>	Type	J	To End Wall
(	500A <sup>(1)</sup>	15	11 (1)	SG	Vertical	16
[	300A <sup>(2)</sup>	15	11 (1)	SK	Vertical	18

(1) Box width is 30" and 7.81" deep

#### Wiring Space - Branch Circuit Breakers

Branch Circuit Devices	Frame	No. of Poles	Minimum Wiring Spaces To Side Wall (30" Wide Box)
Double Branched Bolt-on Devices	TEY/TEYF	1,2,3	9.75"
Horizontal Double Branch Mounted	TED4	2,3	8.25"
Horizontal Double Branch Mounted	SEHA, SELA	2,3	8.25"
Horizontal Single Branch Mounted	SFHA, SFLA	2,3	7.5"
Horizontal Single Branch Mounted	SGHA, SGLA	2,3	8.5"

## **Enclosures**

Panel Size	Box	Front	
Fullel Size	Cat. No. (1)	Size Inches (2)	Cat. No. (3)
0-25.5	AB25BDW	25.5	AF25F,S
28.5-31.5	AB31BDW	31.5	AF31F,S
34.5-37.5	AB37BDW	37.5	AF37F,S
40.5-43.5	AB43BDW	43.5	AF43F,S
46.5-49.5	AB49BDW	49.5	AF49F,S
52.5-55.5	AB55BDW	55.5	AF55F,S
58.5-64.5	AB64BDW	64.5	AF64F,S
67.5-76.5	AB76BDW	76.5	AF76F,S
79.5-82.5	AB82BDW	82.5	AF82F,S
85.5-88.5	AB88BDW	88.5	AF88F,S

- (1) "B" suffix provides blank end walls. Order "K" suffix for endwalls with knockouts.
- (2) Standard boxes are 30" wide by 7.81" deep.
- (3) Flush fronts are 1 1/2" larger than box. Surface fronts are 1/4" larger.

#### **Box Options**

	Cat. No. Suffix (1)
Painted Box	Р
30" wide (2)	W
NEMA 3R/12/4S/4X	3 or 4
NEMA 4X (316 Stainless Steel)	4S

- (1) Add to base box product number.
- (2) Includes field installable gutter barrier.

#### **Permanent Circuit Number Kits**

Description	Cat. No.
1-48	APN48
43-84	APN84
85-126	APN126

## **Front Options**

Tront options	
Description	Cat. No. Suffix (1)
Screw cover	С
Front hinged to box	D
Yale 5116 w/Rosette Lock	Υ
Corbin 15767 Lock	L
GE 75 Key Lock	Е
Corbin 60 Key Lock	J
Door within a door (2)	Р
Stainless steel (3)	S
30" wide	W
Nameplate	N
Screw on nameplate	U
Metal directory	М

- (1) Add to base front catalog number.
- (2) Consists of two lockable doors—one over panel interior and one over box wiring gutters. Yale locks not available.
- (3) Flush only. Available with C and N options.

#### **Stainless Steel Enclosures**

Dimen	sions (i	nches)	Cat No.		
Н	W	D	UL Standard	CSA Labeled	
25.5	30	8	AB254DWS	AB254DWAS	
31.5	30	8	AB314DWS	AB314DWAS	
37.5	30	8	AB374DWS	AB374DWAS	
43.5	30	8	AB434DWS	AB434DWAS	
49.5	30	8	AB494DWS	AB494DWAS	
55.5	30	8	AB554DWS	AB554DWAS	
64.5	30	8	AB644DWS	AB644DWAS	
76.5	30	8	AB764DWS	AB764DWAS	