

Cord Grip Fittings

Color-Coded 90° Cord Grip Strain Relief Connectors

Click brand for more product info ↓
Allied Tube & Conduit



Features:

- Neoprene grommet for a moisture proof seal
- Simple installation, cord can be installed without disassembly of the fitting
- Liquidtight/Oiltight/Raintight
- Suitable for NEMA 4 enclosures and other wet locations
- Male tapered thread NPT
- Colored grommet allows for easy identification of cable range
- RoHS compliant

Standard Materials:

- Malleable Iron/Ductile Iron body and gland nut
- Neoprene grommet

Standard Finish:

- Zinc plated body, gland nut

Certifications & Compliances:

- UL Standard: 514B
- Fed. Spec. A-A-50552
- UL Listed File #E240397

Applications:

- To secure and seal cords or cables entering enclosures or raceways



Part Number	Trade Size	Color Code	Cable Range		Inner Pack	Master Pack	Weight Per 100
	(in)		Min. (in)	Max. (in)			(lb)
CG50-25090KON	1/2	Red	0.15	0.25	25	100	29.2
CG50-35090KON	1/2	White	0.25	0.35	25	100	29.6
CG50-45090KON	1/2	Blue	0.35	0.45	25	100	29.0
CG50-56090KON	1/2	Green	0.45	0.56	25	100	29.0
CG50-65090KON	1/2	Brown	0.55	0.65	25	100	28.5
CG75-25090KON	3/4	Red	0.15	0.25	10	50	46.4
CG75-35090KON	3/4	White	0.25	0.35	10	50	48.3
CG75-45090KON	3/4	Blue	0.35	0.45	10	50	45.4
CG75-56090KON	3/4	Green	0.45	0.56	10	50	45.3
CG75-65090KON	3/4	Brown	0.55	0.65	10	50	45.7
CG75-75090KON	3/4	Yellow	0.65	0.75	10	50	45.7
CG75-85090KON	3/4	Purple	0.75	0.85	10	50	42.7
CG100-56090KON	1	Green	0.45	0.56	5	25	66.1
CG100-65090KON	1	Brown	0.50	0.65	5	25	67.8
CG100-75090KON	1	Yellow	0.65	0.75	5	25	65.7
CG100-85090KON	1	Purple	0.75	0.85	5	25	63.7
CG100-95090KON	1	Gray	0.85	0.95	5	25	71.3
CG100-105090KON	1	Black	0.95	1.05	5	25	70.9

This chart is intended for use as a guide only. Whenever possible, exact cord dimensions should be used. Allied Tube & Conduit assumes no liability for errors, omissions or dimensional changes which may result from changes in design, material or the manufacturing process and which may affect cord and fitting compatibility.

table continued on next page