


HR-LED211E

2" LEDme® Downlight



WAC LIGHTING
Responsible Lighting™



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Round recessed trim with interior open reflector. IC-Rated housing included with trim, can be used as new construction or remodel. Includes one 3W LED.

FEATURES

- 1" aperture
- Cutout: 2 1/2"
- Less than 1/16" thick, super low profile die-cast aluminum trim
- Sold as new construction, may be re-configured in the field for remodel
- Narrow flood beam spread
- 25° visual cut-off angle
- 3000K and 4500K color temperatures
- 50,000 hour rated life
- UL and CUL Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Model #	Color Temp	Watt	Lumens	Efficacy	CRI
HR-LED211E-W	3000K	4W	117	29.3 Lm/W	80
HR-LED211E-C	4500K	4W	130	32.5 Lm/W	75

SPECIFICATIONS

Construction: Die-cast aluminum trim and aluminum heat sink. Housing and junction box are 20 gauge steel painted black. Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120VAC/60Hz input, 4W max output. Power factor >0.9. Dimming with thermal protection.

Light Source: Includes one 3W ANSI compliant Warm/Neutral LED for the finest color consistency possible. Replacement modules available.

Dimming: May be dimmed to 5% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from 15"-24 1/2" to accommodate various joist constructions and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. For remodel installation, three heavy gauge inner retention clips push out onto ceiling or other mounting surface to firmly hold housing in place. Accommodates surface up to 1" thick. Minimum plenum height of 4" required. 2 1/2" cutout hole.

Trim Finish: Abrasion resistant powder coat paint finish in White (WT).

Rating: IC-Rated: Suitable for direct contact with insulation.

Standards: UL & CUL Listed.

ORDER NUMBER

Model #	Color Temp	Finish
HR-LED211E	W 3000K C 4500K	WT White

REPLACEMENT MODULES

Model #	Watt	Color Temp
RM1X3-30-DL	1 x 3W	3000K
RM1X3-45-DL	1 x 3W	4500K

HR-LED211E - - WT

Example: HR-LED211E-C-WT

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585


Headquarters/Eastern Distribution Center
615 South Street • Garden City, NY 11530
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
168 Brea Canyon Road • City of Industry, CA 91789
Phone (909) 468.1848 • Fax (909) 468.9958

HR-LED211E

2" LEDme® Downlight

PHOTOMETRICS – 4W 4500K Open Trim



PHOTOMETRICS – 4 W 3000K Open Trim

