


HR-LED411TL – Invisible Trim™

4" LEDme® Open Reflector Downlight Trim



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Round recessed trim with interior open reflector. Designed to sit flush with the ceiling for a clean, architectural look. For use with HR-LED418 Invisible Trim™ series housings.

FEATURES

- Flush mount, no profile die-cast aluminum trim
- Recessed depth from LEDs to trim edge is 2 3/8"
- Narrow flood beam spread
- Deep regression produces a very low glare with 40° cut-off angle
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

Light Source: Utilizes six 3W LED's (included with housing). See individual housing for wattage rating.

Finish: Abrasion resistant powder coat painted or plated metal finish. Baffle is available in Black (BK) or White (WT). Trim is available in Black (BK), Brushed Nickel (BN), or White (WT).

Standards: UL & CUL Listed.

ORDER NUMBER

Model #	Finish	Baffle/Trim
HR-LED411TL	BK/BN	Black/Brushed Nickel
	BK/WT	Black/White
	WT/WT	White/White

FINISHES

BK/BN



BK/WT



WT/WT



HR-LED411TL –

Example: HR-LED411TL-BK/BN

COMPATIBLE HOUSINGS

Model #	Installation Type	Color Temp	Lumens	CRI	Input	Wattage	Current	Dimensions
HR-LED418-NIC-ROW	New Construction – IC-Rated	3000K	380	80	120V 50/60Hz	11W max	450mA	L: 15-24 1/2" W: 6 3/4" H: 5 1/2"
HR-LED418-N-ROW	New Construction – Non-IC	3000K	480	80	120V 50/60Hz	18W max	700mA	L: 15-24 1/2" W: 6 3/4" H: 5 1/2"
HR-LED418-NIC-ROC	New Construction – IC-Rated	4500K	457	75	120V 50/60Hz	11W max	450mA	L: 15-24 1/2" W: 6 3/4" H: 5 1/2"
HR-LED418-N-ROC	New Construction – Non-IC	4500K	600	75	120V 50/60Hz	18W max	700mA	L: 15-24 1/2" W: 6 3/4" H: 5 1/2"
HR-LED418-RIC-ROW	Remodel – IC-Rated	3000K	380	80	120V 50/60Hz	11W max	450mA	L: 11 7/8" W: 6 3/8" H: 5 5/8"
HR-LED418-R-ROW	Remodel – Non-IC	3000K	480	80	120V 50/60Hz	18W max	700mA	L: 11 7/8" W: 6 3/8" H: 5 5/8"
HR-LED418-RIC-ROC	Remodel – IC-Rated	4500K	457	75	120V 50/60Hz	11W max	450mA	L: 11 7/8" W: 6 3/8" H: 5 5/8"
HR-LED418-R-ROC	Remodel – Non-IC	4500K	600	75	120V 50/60Hz	18W max	700mA	L: 11 7/8" W: 6 3/8" H: 5 5/8"

See individual housing spec sheets for complete information.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

615 South Street • Garden City, NY 11530

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

168 Brea Canyon Road • City of Industry, CA 91789

Phone (800) 526.2588 • Fax (800) 526.2585