

MT-230MH


2 Light PAR30 Metal Halide Multiple Spot



WAC LIGHTING
Responsible Lighting™



14 $\frac{7}{8}$ " × 8 $\frac{1}{8}$ "




9 $\frac{7}{8}$ "

23 $\frac{3}{4}$ "



14 $\frac{1}{8}$ " × 7 $\frac{1}{8}$ "



8 $\frac{3}{4}$ "

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Rectangle two light gimbal ring style adjustable recessed fixture, available with trim or Invisible Trim™, designed to sit flush with the ceiling for a clean, architectural look. Housing and trim ordered separately.

FEATURES

- Integrates high output, excellent light quality and superb energy efficiency in a compact package equal in size to an MR16 halogen
- Provides improved discharge arc offering excellent color stability and color rendering
- Best choice for retail applications where there is minimal on/off operation
- Trim version has a $\frac{1}{4}$ " low profile, Invisible Trim™ sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 25° vertical adjustment and 350° horizontal rotation
- 20W, 39W or 70W lamping
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Stamped metal trim and aluminum housing. Frame, junction box and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch and chain wiring.

Ballast: Pulse start electronic ballast, 120V/277AC input. Thermal protection provided to prevent against overheating and misuse of insulation near fixture.

Light Source: Utilizes one 20W, 39W or 70W PAR30L metal halide lamp. Lamp sold separately.

Mounting: Supplied with hanger bars, adjustable from 15"-24 $\frac{1}{2}$ " to accommodate various joist construction and grid sizes. Accommodates surface of $\frac{1}{2}$ " to 1" thick. 7 $\frac{3}{16}$ " × 13 $\frac{5}{16}$ " cutout with trim, 7 $\frac{5}{8}$ " × 14 $\frac{1}{16}$ " cutout for Invisible Trim™.

Finish: Powder coat paint in White Trim/Black Baffle (WT/BK) and White Trim/White Baffle (WT/WT).

Rating: Non-IC: Insulation must be kept at least 3" away from housing.

Standards: UL & CUL Listed. Suitable for damp locations.

TRIM ORDER NUMBER

Model #	Finish – Trim/Baffle
MT-230	WT/BK White/Black WT/WT White/White

FINISHES

WT/BK



WT/WT



HOUSING ORDER NUMBER

Model #	Watt
MT-230MH	20 20W 39 39W 70 70W

MT-230

–

Example: **MT-230-WT/WT**

MT-230MH

–

Example: **MT-230MH-39**

INVISIBLE TRIM™ ORDER NUMBER

MT-230TL

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
615 South Street • Garden City, NY 11530
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
168 Brea Canyon Road • City of Industry, CA 91789
Phone (800) 526.2588 • Fax (800) 526.2585