

Standard Fitting Dimensions

Width:	1-5/8"	(41.3 mm)
Thickness:	1/4"	(6.3 mm)
Hole Diameter:	9/16"	(14.3 mm)
Hole Spacing On Center:	1-7/8"	(47.6 mm)
Hole Spacing From Ends:	13/16"	(20.6 mm)
Metrics in Parenthesis		
•Unless Otherwise Specified•		

VERSABAR CORPORATION

RIGHT ANGLE FITTINGS



VF-2308 Wt/ea .62 Lbs. (.280 kg.) 	VF-2213 Wt/ea .85 Lbs. (.384 kg.) 	VF-2322 Wt/ea .81 Lbs. (.366 kg.) 	VF-2313 Wt/ea 1 Lb. (.452 kg.)
VF-2315-R* Wt/ea .58 Lbs. (.262 kg.) VF-2315-L 	VF-2301-R* Wt/ea .62 Lbs. (.280 kg.) VF-2301-L 	VF-2310 Wt/ea .75 Lbs. (.339 kg.) 	VF-2407 Wt/ea .84 Lbs. (.379 kg.)
VF-2407-B Wt/ea .74 Lbs. (.334 kg.) 	VF-2403 Wt/ea .84 Lbs. (.379 kg.) 	VF-2426-R* Wt/ea 1.2 Lbs. (.542 kg.) VF-2426-L 	VF-2417 Wt/ea .75 Lbs. (.339 kg.)
VF-2411-R* Wt/ea 1.06 Lbs. (.479 kg.) VF-2411-L 	VF-2421-R* Wt/ea 1 Lb. (.453 kg.) VF-2421-L 	VF-2410 Wt/ea 1.08 Lbs. (.488 kg.) 	VF-2402-R Wt/ea .83 Lbs. (.375 kg.) VF-2402-L*

* Right Hand Version Illustrated, Left Opp.

* Right Hand Version Illustrated, Left Opp.

* Right Hand Version Illustrated, Left Opp.

* Left Hand Version Illustrated, Right Opp.